



PRODUCT PERFORMANCE REPORT

Document ID 1447924894

Issued on November 19th, 2015

PROJECT IDENTIFICATION - This product performance report is delivered for:

Name **Panasonic**
Company **Panasonic**
Project reference **Panasonic**
Project location **Germany**

PRODUCT IDENTIFICATION

Certification Diploma N° **15.02.216**
Brand **PANASONIC**
Range **AQUAREA Monobloc T-CAP Réversible**
Product reference **WH-MXC16G9E8**

Important notice:

- I. Data featured in this report are valid at the date of issue. The scope of this product performance report does not include all certified data that can be checked at <http://www.eurovent-certification.com>
- II. This product performance report is valid only for above product features and should not be referred to as a Diploma.

FEATURE	VALUE	UNIT
Acoustics		
External Side Sound Enveloppe	72.0	dB(A)
General information		
Current Type	400	V
Phase	THREE PHASED	
Frequency	50	Hz
Liquid Refrigerant	R410A	
Type [Packaged, Split, Multisplit]	Monobloc	
Family [Aerothermal, ...]	aerothermal	
Location [Indoor, Outdoor]	outdoor	
Compressor type [Scroll, Screw, ...]	Rotary	
Compressor system [Bi-compressor, ?]	mono-compressor	
Reversible [TRUE or FALSE]	true	
NF Certificate number & revision	1273	
Thermal performance Air -7°C Water 30/35 °C		
Pe @ Air -7°C Water 30-35°C	6.42	kW
Ph @ Air -7°C Water 30/35°C	16.0	kW
COP @ Air -7°C Water 30-35°C	2.49	
Thermal performance Air -7°C Water 40/45 °C		
Pe @ Air -7°C Water 40-45°C	7.57	kW
Ph @ Air -7°C Water 40-45°C	16.0	kW
COP @ Air -7°C Water 40-45°C	2.11	
Thermal performance Air 2°C Water 30/35 °C		
Ph @ Air 2°C Water 30-35°C	16.0	kW
Pe @ Air 2°C Water 30-35°C	5.21	kW



PRODUCT PERFORMANCE REPORT

Document ID 1447924894

Issued on November 19th, 2015

FEATURE	VALUE	UNIT
COP @ Air 2°C Water 30-35°C	3.07	
Thermal performance Air 2°C Water 40/45 °C		
Ph @ Air 2°C Water 40-45°C	16.0	kW
Pe @ Air 2°C Water 40-45°C	6.31	kW
COP @ Air 2°C Water 40-45°C	2.54	
Thermal performance Air 7 °C Water 30-35 °C		
Pe @ Air 7°C Water 30/35°C	3.74	kW
Ph @ Air 7°C Water 30-35°C	16.0	kW
COP @ Air 7°C Water 30/35°C	4.28	
Thermal performance Air 7°C Water 40/45 °C		
Ph_Air @ 7 Water 40-45	16.0	kW
COP @ Air 7°C Water 40-45°C	3.33	